

GVD-126

10.4" Video display

Rugged touchscreen GVA display with DEF Stan 23-09 compliant design

Real-time video imaging for C4ISR and GVA compliance with ergonomics and optimized SWaP-C.



The GVD-126 GVA video display combines a rugged 10-inch touchscreen with real-time video imaging to provide a high-performance visualization display in a compact footprint. The GVD-126 display is compliant with the Generic Vehicular Architecture (GVA) and optimized for SWaP-C and modular open architecture, making this display ideal for vehicle-mounted C4ISR applications.

Extreme performance

The GVD-126 display delivers the latest proven technologies, such as a rugged analog-resistive, low-reflection touchscreen, and real-time video stream decoding for tactical network architectures. These features are packaged to perform while operating in harsh environments.

Modular design

The GVD-126 smart display includes expansion slots based on open industry standards. This modularity allows customized IO configurations and dedicated hardware controllers.

Image processing and computing performance

The GVD-126 unit connects to a variety of network stream, analog video, and data sources to deliver enhanced situational awareness. For a smart-display configuration with an open-architecture CPU, ScioTeq also offers the SmartView SV-126 display.



Product specifications	
Panel size	10.4"; 4:3 aspect ratio
Panel resolution	1024 x 768 (XGA)
Weight	5.9 kg / 13 lbs
Dimensions	286 x 254 x 68 mm / 11.25 x 10.0 x 2.66 inches (w x h x d)
Brightness	Day mode: 686 cd/m ² / 200 fL min. Night mode: 3.43 cd/m ² / 1.0 fL max., dimmable to black
Dimming ratio	> 200:1 typical
Contrast ratio	900:1 (dark environment)
Viewing angle	85° horizontal and vertical
Video inputs & outputs	Def Stan 23-09 compliant connectors 1 x VIVOE Gigabit Ethernet port 1 x DVI-D 1.0 video port 1 x USB 2.0 touchscreen port 1 x USB 2.0 remote-control port 1 x Maintenance Ethernet port 8 x Multiplexed GPIO digital discrete inputs 3 x Digital GPIO discrete outputs
Optional inputs & outputs	3x video inputs RS-170, PAL/NTSC
Command & control	Def Stan 23-09 compliant bezel, 4 control keys and 28 function keys Rugged AR high-resolution touchscreen
Connectors	DEF STAN 23-09 compliant
Power	MIL-STD-1275E compliant
Power consumption	50 W typical, 80 W max. (without heaters)
Operating temperature	-46° to +65° C (+71° C with limitations)
Storage temperature	-51° to +71° C
Relative humidity	95 percent, 60° C
Vibration	Tracked-vehicle profile
Shock	40 g, 23 ms (6 shocks/axis)
EMI / EMC	MIL-STD-461F, Ground army
Drip proof	IPX7
Altitude	40,000 feet operating, 50,000 feet non-operating
Sand & dust, salt fog	48 hours, 5-percent concentration, blowing sand/dust
Cooling	Passive
Smart display configuration	Refer to ScioTeq's SV-126 literature for optional smart display, featuring the latest Intel® Core™ CPU's.

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED

The information and data given are typical for the equipment described. However any individual item is subject to change without any notice.

STQ_D&S_GVD-126_SpecSheet_210426

WWW.SCIOTEQ.COM

